



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/575,120	04/07/2006	Ryoji Nomura	0553-0492	9220
26568	7590	05/10/2010		
COOK ALEX LTD SUITE 2850 200 WEST ADAMS STREET CHICAGO, IL 60606			EXAMINER CROUSE, BRETT ALAN	
			ART UNIT	PAPER NUMBER
			1786	
			MAIL DATE	DELIVERY MODE
			05/10/2010	PAPER

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

<b>Office Action Summary</b>	<b>Application No.</b> 10/575,120	<b>Applicant(s)</b> NOMURA ET AL.	
	<b>Examiner</b> Brett A. Crouse	<b>Art Unit</b> 1786	

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 06 April 2010.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-14 is/are pending in the application.
- 4a) Of the above claim(s) 3-5 is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1, 2 and 6-14 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☒ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☒ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☒ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |   |   |
|---|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)   | 4) <input type="checkbox"/> Interview Summary (PTO-413)<br>Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftperson's Patent Drawing Review (PTO-948)   | 5) <input type="checkbox"/> Notice of Informal Patent Application                       |
| 3) <input checked="" type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)<br>Paper No(s)/Mail Date <u>20100406</u> . | 6) <input type="checkbox"/> Other: _____  |

## **DETAILED ACTION**

### ***Application Status***

1. This office action is in response to the amendment, filed 6 April 2010, which amends claims 1-5 and 9. Claims 1-14 are pending.

### ***Response to Amendment***

2. The rejection of claims 1, 2, 6, 7, 8, 9, 10, 14 under 35 U.S.C. 102(b) as being anticipated by Heeney et al., EP 1,439,590, is overcome by the amendment, filed 6 April 2010.
3. The rejection of claims 1-6, 9-14 under 35 U.S.C. 103(a) as being unpatentable over Takasu et al., US 2004/0258954 in view of Heeney et al., EP 1,439,590 with further evidence provided by Angelopoulos et al., US 5,198,153, is overcome by the amendment, filed 6 April 2010.
4. The rejection of claims 7, 8 under 35 U.S.C. 103(a) as being unpatentable over Takasu et al., US 2004/0258954 in view of Heeney et al., EP 1,439,590 with further evidence provided by Angelopoulos et al., US 5,198,153 as applied to claims 1-6, 9-14 above, and further in view of Hosokawa, US 2002/0045061, is overcome by the amendment, filed 6 April 2010.

Art Unit: 1786

***Claim Rejections - 35 USC § 103***

5. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:


(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

6. Claims 1, 2, 6, 7, 8, 9, 10, 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Heeney et al., EP 1,439,590 in view of Tokito et al., Journal of Physics: Applied Physics, (1996), Volume 29, Pages 2750-2753.

Heeney teaches:

Paragraph [0102], teaches an electroluminescent device comprising mono-, oligo- or poly-mers of formula (I). The passage additionally teaches multilayer electroluminescent device structures comprising hole transport layer(s), electron transport layer(s) and emission layer(s) and applying a voltage across such a structure.

Paragraphs [0026]-[0029], claim 1, formula (I), teach mono-, oligo- or poly-mers of formula (I), shown below, in the charge transport or electroluminescent layers of an organic light emitting diode. The mers of formula (I) can be used alone or in combination. X of formula (I) can be a substituted or unsubstituted arylene or heteroarylene group.



Art Unit: 1786

Paragraph [0079], teaches the compositions comprising mers of formula (I) can further comprise additional materials including transition metal compounds.

Paragraphs [0028] [0030]-[0033], [0080], teach the use of the materials of formula (I) in displays and backlights.

Heeney does not teach:

Heeney does not teach transition metal oxides.

Tokito teaches:

Page 2750, teaches the use of various transition metal oxides to reduce the energy barrier and improve hole injection from an ITO or AZO anode into an electroluminescent device. Vanadium oxide, molybdenum oxide and ruthenium oxide are taught as exemplified materials.

Page 2752, figure 4, teaches the effect on the operating voltage versus the work function of the metal oxide selected.





It would have been obvious to one of ordinary skill in the art to use the transition metal oxides of Tokito as the transition metal compounds suggested by Heeney to obtain the improved charge injection from the ITO electrode of Heeney as observed by Tokito.

7. Claims 1-6, 9-14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takasu et al., US 2004/0258954 in view of Heeney et al., EP 1,439,590 and Tokito et al., Journal of Physics: Applied Physics, (1996), Volume 29, Pages 2750-2753 with further evidence provided by Angelopoulos et al., US 5,198,153.

Takasu teaches:

Art Unit: 1786

Paragraphs [0025]-[0031], formulae 5,6,7,8, teach an electroluminescent device comprising a molecule represented by the formulae, shown below.



Paragraph [0032], teaches Y of the formulae represents an arylene group.

Paragraphs [0098], [0104], [0112], [0121], [0125], [0128], provide exemplified compounds in which further fused rings are formed from  $R^1$ ,  $R^2$  and  $R^3$ ,  $R^4$ .

Paragraph [0059], teaches various electroluminescent device structures. The passage additionally teaches the materials of the formulae can be used in the hole injection, hole transport, and luminescent layers of the device.

Paragraph [0061], teaches various materials suitable for use in the layers of the electroluminescent device.

Paragraphs [0067]-[0068], figures 2A, 2B, teach the use of the electroluminescent device as a pixel

Paragraphs [0086]-[0089], teach the use of the electroluminescent device in various display applications including televisions, personal computers, and telephones.

Art Unit: 1786

Takasu does not teach:


Takasu does not teach an electron acceptor as a dopant to the layer comprising the material of the formulae.

Takasu does not teach the use of the materials of the formulae in the electron transport/injection layers of an electroluminescent device.

Heeney teaches:

Paragraph [0102], teaches an electroluminescent device comprising mono-, oligo- or poly-mers of formula (I). The passage additionally teaches multilayer electroluminescent device structures comprising hole transport layer(s), electron transport layer(s) and emission layer(s) and applying a voltage across such a structure.

Paragraphs [0026]-[0029], [0080], claim 1, formula (I), teach mono-, oligo- or poly-mers of formula (I), shown below, in the charge transport, charge injection, or electroluminescent layers of an organic light emitting diode. The mers of formula (I) can be used alone or in combination. X of formula (I) can be a substituted or unsubstituted arylene or heteroarylene group.



Paragraphs [0077]-[0079], teaches the compositions comprising mers of formula (I) can further comprise additional materials including transition metal compounds. The passage also incorporates by reference, Angelopoulos et al., US 5,198,153 in paragraph [0077].

Paragraphs [0028] [0030]-[0033], [0080], teach the use of the materials of formula (I) in displays and backlights.


Art Unit: 1786

Angelopoulos as further evidence:

Angelopoulos is incorporated by reference into Heeney in paragraph [0077].

Column 17, lines 52-57, teach doped polymers can provide conductivity on the order of  $10 \text{ ohm}^{-1} \text{ cm}^{-1}$ .

Column 16, lines 8-24, formula, teach suitable (co)polymers include thiophenes, furans, pyrroles and combinations thereof. The formula is reproduced below.



It would have been obvious to one of ordinary skill in the art to use the doped thiophene, furan, and pyrrole (co)polymers as taught by Heeney in device of Takasu as charge transporting materials in the light emitting, hole injection/transport and electron injection/transport layers to provide high conductivity to the layer(s) of the device to improve device efficiency.

Takasu / Heeney does not teach:

Takasu / Heeney does not teach transition metal oxides.

Tokito teaches:

Page 2750, teaches the use of various transition metal oxides to reduce the energy barrier and improve hole injection from an ITO or AZO anode into an electroluminescent device. Vanadium oxide, molybdenum oxide and ruthenium oxide are taught as exemplified materials.

Page 2752, figure 4, teaches the effect on the operating voltage versus the work function of the metal oxide selected.



Art Unit: 1786

It would have been obvious to one of ordinary skill in the art to use the transition metal oxides of Tokito as the transition metal compounds suggested by Heeney to obtain the improved charge injection from the ITO electrode of Takasu / Heeney as observed by Tokito.

8. Claims 7, 8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takasu et al., US 2004/0258954 in view of Heeney et al., EP 1,439,590, and Tokito et al., Journal of Physics: Applied Physics, (1996), Volume 29, Pages 2750-2753 with further evidence provided by Angelopoulos et al., US 5,198,153, with further evidence provided by Angelopoulos et al., US 5,198,153 as applied to claims 1-6, 9-14 above, and further in view of Hosokawa, US 2002/0045061.

The teachings of Takasu/Heeney as in the rejection above are relied upon.

Takasu/Heeney does not teach:

Takasu does not teach an electron generation layer.

Hosokawa teaches:

Paragraphs [0109]-[0115], teach a hole barrier layer improves device performance by confining holes in the luminescence layer. The passage additionally provides a preferred composition of the hole barrier layer comprising BPhen or BCP in combination with Li or Cs.

Paragraph [0160], example 3, teaches 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (Bathocuproine)(BCP) co-deposited with cesium in a hole barrier layer deposited upon the luminescent layer.

Art Unit: 1786

Paragraph [0103], teaches it is preferred to include a semiconductor layer having an electrical conductivity of at least  $10^{-10}$  S/cm between the anode and light emitting layer.

It would have been obvious to one of ordinary skill in the art to use the hole barrier layer of Hosokawa in the device of Takasu to improve the hole confinement in the light emitting layer and improve device performance as suggested by Hosokawa.

It would have been obvious to one of ordinary skill in the art to include a layer of the doped material of Takasu/Heeney in the device of Takasu/Heeney between the anode and light emitting layer to provide a high conductivity layer to improve hole injection into the light emitting layer. Such a layer would be expected to meet the limitations of a electron generation layer as indicated on page 18 of the instant specification.

9. Claims 1, 2, 6, 7, 8, 9, 10, 14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Heeney et al., EP 1,439,590 in view of Ikeda et al., WO 2005/031798.


Heeney teaches:

Paragraph [0102], teaches an electroluminescent device comprising mono-, oligo- or poly-mers of formula (I). The passage additionally teaches multilayer electroluminescent device structures comprising hole transport layer(s), electron transport layer(s) and emission layer(s) and applying a voltage across such a structure.

Paragraphs [0026]-[0029], claim 1, formula (I), teach mono-, oligo- or poly-mers of formula (I), shown below, in the charge transport or electroluminescent layers of an organic light emitting diode. The mers of formula (I) can be used alone or in

Art Unit: 1786

combination. X of formula (I) can be a substituted or unsubstituted arylene or heteroarylene group.



Paragraph [0079], teaches the compositions comprising mers of formula (I) can further comprise additional materials including transition metal compounds.

Paragraphs [0028] [0030]-[0033], [0080], teach the use of the materials of formula (I) in displays and backlights.

Heeney does not teach:

Heeney does not teach transition metal oxides.

Ikeda teaches:

Abstract, teaches a light emitting device comprising a layer which further comprises a hole transporting compound and a oxide semiconductor or metal oxide.

Page 3, teaches exemplified examples of the oxide semiconductor or metal oxide. The examples include vanadium oxide, molybdenum oxide, tungsten oxide and ruthenium oxide.





It would have been obvious to one of ordinary skill in the art to use the transition metal oxides of Ikeda as the transition metal compounds suggested by Heeney to obtain the improved charge transportation and improved device life as observed by Ikeda.

Art Unit: 1786

10. Claims 1-6, 9-14 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takasu et al., US 2004/0258954 in view of Heeney et al., EP 1,439,590 and Ikeda et al., WO 2005/031798, with further evidence provided by Angelopoulos et al., US 5,198,153.

Takasu teaches:

Paragraphs [0025]-[0031], formulae 5,6,7,8, teach an electroluminescent device comprising a molecule represented by the formulae, shown below.



Paragraph [0032], teaches Y of the formulae represents an arylene group.

Paragraphs [0098], [0104], [0112], [0121], [0125], [0128], provide exemplified compounds in which further fused rings are formed from R<sup>1</sup>, R<sup>2</sup> and R<sup>3</sup>, R<sup>4</sup>.

Paragraph [0059], teaches various electroluminescent device structures. The passage additionally teaches the materials of the formulae can be used in the hole injection, hole transport, and luminescent layers of the device.

Paragraph [0061], teaches various materials suitable for use in the layers of the electroluminescent device.

Art Unit: 1786

Paragraphs [0067]-[0068], figures 2A, 2B, teach the use of the electroluminescent device as a pixel

Paragraphs [0086]-[0089], teach the use of the electroluminescent device in various display applications including televisions, personal computers, and telephones.

Takasu does not teach:


Takasu does not teach an electron acceptor as a dopant to the layer comprising the material of the formulae.

Takasu does not teach the use of the materials of the formulae in the electron transport/injection layers of an electroluminescent device.

Heeney teaches:

Paragraph [0102], teaches an electroluminescent device comprising mono-, oligo- or poly-mers of formula (I). The passage additionally teaches multilayer electroluminescent device structures comprising hole transport layer(s), electron transport layer(s) and emission layer(s) and applying a voltage across such a structure.

Paragraphs [0026]-[0029], [0080], claim 1, formula (I), teach mono-, oligo- or poly-mers of formula (I), shown below, in the charge transport, charge injection, or electroluminescent layers of an organic light emitting diode. The mers of formula (I) can be used alone or in combination. X of formula (I) can be a substituted or unsubstituted arylene or heteroarylene group.



Art Unit: 1786

Paragraphs [0077]-[0079], teaches the compositions comprising mers of formula (I) can further comprise additional materials including transition metal compounds. The passage also incorporates by reference, Angelopoulos et al., US 5,198,153 in paragraph [0077].


Paragraphs [0028] [0030]-[0033], [0080], teach the use of the materials of formula (I) in displays and backlights.

Angelopoulos as further evidence:

Angelopoulos is incorporated by reference into Heeney in paragraph [0077].

Column 17, lines 52-57, teach doped polymers can provide conductivity on the order of  $10 \text{ ohm}^{-1} \text{ cm}^{-1}$ .

Column 16, lines 8-24, formula, teach suitable (co)polymers include thiophenes, furans, pyrroles and combinations thereof. The formula is reproduced below.



It would have been obvious to one of ordinary skill in the art to use the doped thiophene, furan, and pyrrole (co)polymers as taught by Heeney in device of Takasu as charge transporting materials in the light emitting, hole injection/transport and electron injection/transport layers to provide high conductivity to the layer(s) of the device to improve device efficiency.

Takasu / Heeney does not teach:

Takasu / Heeney does not teach transition metal oxides.

Ikeda teaches:

Art Unit: 1786

Abstract, teaches a light emitting device comprising a layer which further comprises a hole transporting compound and a oxide semiconductor or metal oxide.

Page 3, teaches exemplified examples of the oxide semiconductor or metal oxide. The examples include vanadium oxide, molybdenum oxide, tungsten oxide and ruthenium oxide.

It would have been obvious to one of ordinary skill in the art to use the transition metal oxides of Ikeda as the transition metal compounds suggested by Heeney to obtain the improved charge transportation and improved device life as observed by Ikeda.

11. Claims 7, 8 are rejected under 35 U.S.C. 103(a) as being unpatentable over Takasu et al., US 2004/0258954 in view of Heeney et al., EP 1,439,590, and Ikeda et al., WO 2005/031798, with further evidence provided by Angelopoulos et al., US 5,198,153, with further evidence provided by Angelopoulos et al., US 5,198,153 as applied to claims 1-6, 9-14 above, and further in view of Hosokawa, US 2002/0045061.

The teachings of Takasu/Heeney as in the rejection above are relied upon.

Takasu/Heeney does not teach:

Takasu does not teach an electron generation layer.

Hosokawa teaches:

Paragraphs [0109]-[0115], teach a hole barrier layer improves device performance by confining holes in the luminescence layer. The passage additionally provides a preferred composition of the hole barrier layer comprising BPhen or BCP in combination with Li or Cs.

Art Unit: 1786

Paragraph [0160], example 3, teaches 2,9-dimethyl-4,7-diphenyl-1,10-phenanthroline (Bathocuproine)(BCP) co-deposited with cesium in a hole barrier layer deposited upon the luminescent layer.

Paragraph [0103], teaches it is preferred to include a semiconductor layer having an electrical conductivity of at least  $10^{-10}$  S/cm between the anode and light emitting layer.

It would have been obvious to one of ordinary skill in the art to use the hole barrier layer of Hosokawa in the device of Takasu to improve the hole confinement in the light emitting layer and improve device performance as suggested by Hosokawa.

It would have been obvious to one of ordinary skill in the art to include a layer of the doped material of Takasu/Heeney in the device of Takasu/Heeney between the anode and light emitting layer to provide a high conductivity layer to improve hole injection into the light emitting layer. Such a layer would be expected to meet the limitations of a electron generation layer as indicated on page 18 of the instant specification.

### ***Response to Arguments***

12. Applicant's arguments have been considered but are moot in view of the new ground(s) of rejection.



Art Unit: 1786

13. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a).

Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

### ***Contact Information***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Brett A. Crouse whose telephone number is (571)-272-6494. The examiner can normally be reached on Monday - Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, D. Lawrence Tarazano can be reached on 571-272-1515. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 1786

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/B. A. C./  
Examiner, Art Unit 1794

/D. Lawrence Tarazano/  
Supervisory Patent Examiner, Art Unit  
1786